



5 Tonne Clear Floor 2 Post "Asymmetric Design"

Manufactured In Korea, the new Powerrex SL25TF 2 Post vehicle hoist is the latest addition to the Powerrex 2 post range. With it's 5 Tonne lift capacity, and extra wide design, the SL25TF is an all rounder model allowing the technician to work upon small passenger vehicles right through to 4WD and light commercials.

*New Model With
5 Tonne Lift
Capacity*

*Approved To The
Australian Standard
AS/NZS1418:9*

*Extra-Wide Body,
Asymmetric
Design*

*Ideal For Small
Cars, 4WD & Light
Commercials*

Powerrex SL25TF *2 Post Vehicle Hoist*

Powerrex SL25TF

Hoist Features

- **New 5 Tonne Model**
- Designed & Manufactured In South Korea
- "Extra" Wide Between Posts - Great For Large Vehicles
- Asymmetric Design
- 3 Stage Front Arms
- 2 Stage Adjustable Load Pads
- Solid Automatic Arm Locks
- Dual Hydraulic Rams
- Roof Protection Bar
- Twin Balance Cables
- Positive Safety System
- Powder Coat Finish
- Ideal For Small Passenger Vehicles, 4WD & Light Commercial



Roof Protection Bar

A padded roof bar with an automatic limit switch installed prevents high vehicles from making contact with the bridge.



Solid Automatic Arm Locks

As soon as the vehicle is lifted from the ground the gear type locks lock into place to prevent the arm from moving.



Two Stage Adjustable Load Pads

The adjustable load pad stools allow the pad height to be easily wound up or down to suit the vehicle to be lifted. Pad Stool Height 130 - 210 mm.



Control Box

With a three button control box the technician can operate the entire hoist at the touch of a button.

Includes Up, Down & Lock Button.

Specifications	SL25TF
Max. Lift Capacity	5000 kg
Max. Lift Height	1850 - 1930 mm
Pad Stool Height	130 – 210 mm
Overall Height	3850 mm
Overall Width (W/Outrigger)	3660 mm
Width Between Posts	2860 mm
Power Supply	415 Volt

Also Consider

Powerrex 4 Tonne 2 Post Range

